DEKS
A Skellerup Industries Company

20 YEAR WARRANTY



Dektite® Original

The original watertight flashing for metal roof penetrations

BSI™
FS 520679
IN QUALITY ISO 9001

UPC®

- **Easy to identify**
  Dektite brand name engraved on product for traceability
- **Unique cone design**
  Provides 10mm (1/2") continuous contact with flashed pipe providing a watertight seal
- **Clear markings in metric and imperial measures**
  Makes for easier cutting to pipe size
- **Proven design**
  Associated with the roofing industry globally for over 40 years
- **Size ranges - Numbers 0-9**
  Available in Black and Grey EPDM, and red silicone
- **Twenty year warranty**
  Just fit it and forget it - we've got you covered

www.deks.com.au

A Skellerup Industries Company

Selection Guide

DEKS Code			Description	Pipe OD		Base OD		Pitch	Carton QTY
Black EPDM	Grey EPDM	Red Silicone		mm	inch	mm	inch		
DF100B	DF100G	DF200RE	Dektite Original #0	0 - 35	0 - 1⅜"	93	3¾"	0-40° or 10/12	40
DF101B	DF101G	DF201RE	Dektite Original #1	5 - 60	¼ - 2½"	124	4¾"	0-40° or 10/12	10
DF102B	DF102G	DF202RE	Dektite Original #2	45 - 80	1¾ - 3¼"	162	6½"	0-40° or 10/12	10
DF103B	DF103G	DF203RE	Dektite Original #3	5 - 127	¼ - 5"	202	8"	0-40° or 10/12	10
DF104B	DF104G	DF204RE	Dektite Original #4	75 - 160	3 - 6¼"	238	9½"	0-40° or 10/12	10
DF105B	DF105G	DF205RE	Dektite Original #5	108 - 190	4¼ - 7½"	276	11"	0-40° or 10/12	5
DF106B	DF106G	DF206RE	Dektite Original #6	125 - 230	5 - 9"	322	12¾"	0-40° or 10/12	5
DF107B	DF107G	DF207RE	Dektite Original #7	150 - 280	6 - 11"	372	14¾"	0-40° or 10/12	5
DF108B	DF108G	DF208RE	Dektite Original #8	175 - 330	7 - 13"	422	16¾"	0-40° or 10/12	5
DF109B	DF109G	DF209RE	Dektite Original #9	254 - 483	10 - 19"	647	25½"	0-40° or 10/12	1

Available in Black and Grey EPDM or Red Silicone

EPDM will withstand constant temperatures at the roofline of -50°C (-58°F) to 115°C (239°F) and up to 150°C (302°F) intermittently
Red Silicone will withstand constant temperatures at the roofline of -50°C (-58°F) to 200°C (392°F) and up to 250°C (482°F) intermittently

Please Note That the outside temperature of the pipe may be significantly different to the exit temperature of the appliance.

Installation Information



1. Cut Dektite® at appropriate pipe diameter marking.



2. Slide Dektite® flashing down over pipe.



3. Apply sealant on underside of flexible aluminum base.



4. Press Dektite® base into contours of panel configuration.



5. Fasten Dektite® to surface with long -life, self drilling fasteners. Apply additional sealant around base if desired.

- Always use the neutral cure low modulus silicone for sealing
- In corrosive and coastal environments fix using blind aluminium rivets



DEKTITE RETROFIT GREY EPDM



DEKTITE ORIGINAL RED SILICONE

Need to flash a tiled roof? Contact DEKS to discuss the tile roof flashing range.

www.deks.com.au