



Retrofit[®] Original

When it has to flash
around, not over



- ☒ Fast and Efficient installation
Wraps around existing or difficult to access pipes
- ☒ Snaps together in seconds
The built-in crimp means no loose clips or rivets
- ☒ Grips tight and stays tight
Made from DEKS quality polymer compound
- ☒ Our base makes easy work
Aluminium base conforms to roof with ease
- ☒ Twenty year warranty
Just fit it and forget it - we've got you covered



Selection Guide


DEKS Code			Description	Pipe OD		Base		Pitch	Carton QTY
Black EPDM	Grey EPDM	Red Silicone		mm	inch	mm	inch		
RF801B	RF801G	RF801RE	Dektite Retrofit #1	20-70	¾" - 2¾"	160	2½ x 2½"	0 - 40° or ¹⁰ / ₁₂	10
RF802B	RF802G	RF802RE	Dektite Retrofit #2	50 - 190	2 - 7½"	273	4 x 4"	0 - 40° or ¹⁰ / ₁₂	5
RF803B	RF803G	RF803RE	Dektite Retrofit #3	85 - 255	3¼" - 10"	389	4 x 4"	0 - 40° or ¹⁰ / ₁₂	5
	RFS4	RFS24	Dektite Soaker	235 - 425	9¼" - 16¾"	762 x 680	5½ x 5½"	0 - 40° or ¹⁰ / ₁₂	2

Available in Black and Grey EPDM or Red Silicone

EPDM will withstand constant temperatures at the roofline of -50°C (-58°F) to 115°C (239°F) and up to 150°C (302°F) intermittently. Red Silicone will withstand constant temperatures at the roofline of -50°C (-58°F) to 200°C (392°F) and up to 250°C (482°F) intermittently.

Please Note That the outside temperature of the pipe may be significantly different to the exit temperature of the appliance.

Installation Information

-  Trim cone to suit pipe size using sharp tin snips.
-  With clip in downstream position, wrap top of cone around pipe and engage metal teeth in opposing pockets starting at the top.
-  To assist locating clip into pocket, place hand behind seam. Fasten clip with pliers or multitools, working from top to base. Do not over crimp.
-  Apply sealant to underside of Dektite® base and shape to roof by hand.
-  Fasten flashing down and secure clip by placing a fastener either side of clip first.
-  Apply sealant to top of crimp closure and any other potential leak areas.



- Always use the neutral cure low modulus silicone for sealing
- Use 10 x 16 (¾" x ⅝") Hex head self-drilling screws
- In corrosive and coastal environments fix using blind aluminium rivets

Need to flash a square penetration? Contact DEKS to discuss the square flashing range.

